

China Lead Stabilzier L-35 Factory price of plastic pvc calcium zinc heat stabilizer

Specifications :

Price	Contact us
Place of Origin	China
Payment Terms	T/T,L/C,D/P
Delivery Detail	3days--7days

Detail Introduction :

Lead stabilizer for PVC profiles L-35

Description

Lead stabilizer L-35 is compound heat stabilizer used for PVC profiles production.

Key property

Endow the PVC melt with eminent thermal stability
Enhance the dispersibility of fillers in the PVC resin
Improve the whiteness and glossiness performance.

Product index

Item	Index
Appearance	White/yellowish flake/powder
Lead content	34±2%
Moisture Content	?0.5?
Density	1.6~1.9g/cm ³

Recommended application

1. Keep the original formula unchanged. The recommended using dosage is 4~5.5 PHR.
2. Adding Lead stabilizer L-35 together with the PVC resin into the high-speed mixer.
3. Keep the temperature at about 115 ? for 8 ~ 10minutes.
4. If you need to increase/decrease of CaCo3 content or want to adjust the lubrication system

Storage

The product should be stored in cool and dry surroundings.
The shelf life is two years, it can be still used if qualified by inspection after shelf life.

Package

25KG/bag with PP bag and PE inner or Kraft paper bag.
600KG/bag Woven bag.