

Lead Stabilzier L-25 Used For PVC Heat Stabilizer Hydrotalcite

Specifications :

Price	Contact us
Model Number	L-25
Place of Origin	China
Min.Order Quantity	1
Payment Terms	T/T,L/C,D/P
Delivery Detail	3days--7days

Detail Introduction :

Lead Stabilizer L-25

Description

Lead stabilizer L-25 is a high efficiency and multifunctional heat stabilizer. It is widely applied in PVC foaming board, pipe, pipe fitting, WPC, foamed sheet and other PVC products.

Key property

It has very good dispersibility and compatibility in PVC system. And it has good thermal stability, good rheological performance, wide range for processing, long period for mold cleaning, etc.

Product index

Specification	Unit	L-25
Appearance	--	flake
Color	--	Cream
Whiteness	--	?92°
Specific gravity	g/cm3	1.45-1.55g/cm3
Lead Content	%	24-30

Reference formula

Item	Cabinet board	Poster board
PVC	75kg	50kg
CaCO3	50kg	35kg
Recycle	30kg	20kg
Foaming Regular P-600	8kg	4.8kg
LU-60	0.5kg	0.4kg
AC	0.4kg	0.3kg
NC	1.2kg	0.6kg
Lead Stabilizer L-25	4.5kg	3.0kg
TiO2	2.5kg	2.0kg

316A	0.4kg	0.28kg
PE wax	0.35kg	0.25kg
Whitening agent	0.03kg	0.03kg